



Industrial Pipe
SCH 40 & SCH 80 PVC, CPVC

TYPE I PVC 1120-1220 SCHEDULE 80 PIPE
 Complies with ASTM D 1785 and Product Standard PS 21-70

Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
001802	1/8"	38.92	500	5000	5.8	1230	0.405"	0.215"	.095"
002802	1/4"	47.02	500	5000	9.8	1130	0.540"	0.300"	.119"
004802	3/8"	64.86	500	5000	13.6	915	0.675"	0.423"	.126"
005802	1/2"	33.31	400	5000	20	850	0.840"	0.546"	.147"
007802	3/4"	45.82	300	4000	27.2	690	1.050"	0.742"	.154"
010802	1"	66.93	200	3000	40.2	630	1.315"	0.957"	.179"
012802	1 1/4"	92.07	100	2500	55.3	520	1.660"	1.278"	.191"
015802	1 1/2"	111.87	100	2000	67.2	470	1.900"	1.5"	.200"
020802	2"	154.83	100	1500	93	400	2.375"	1.939"	.218"

HI TEMP CPVC SCHEDULE 40 PIPE
 DO NOT THREAD
 Complies with ASTM D 1784; ASTM F-441; Commercial Standard CS-207-60

Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
C002402	1/4"	78.59	500	5,000	8.7	780	0.540"	0.364"	.088"
C004402	3/8"	103.26	500	5,000	11.7	620	0.675"	0.493"	.091"

HI TEMP CPVC SCHEDULE 80 PIPE

Part Number	Pipe Size	List Per 100 ft.	Ft. Per Bundle	Ft. Per Lift	Weight Per 100 ft.	Pressure Rating	Outside Diameter	Inside Diameter	Minimum Wall
C001802	1/8"	69.12	500	5,000	6.3	1230	0.405"	0.215"	.095"
C002802	1/4"	95.25	500	5,000	10.9	1130	0.540"	0.300"	.119"
C004802	3/8"	113.05	500	5,000	15.2	915	0.675"	0.423"	.126"
C005802	1/2"	154.13	400	5,000	24.6	850	0.840"	0.546"	.147"
C007802	3/4"	211.17	300	4,000	30.4	690	1.050"	0.742"	.154"
C010802	1"	308.24	200	3,000	46.0	630	1.315"	0.957"	.179"
C012802	1 1/4"	427.12	100	2,500	61.8	520	1.660"	1.278"	.191"
C015802	1 1/2"	516.63	100	2,000	75.1	470	1.900"	1.500"	.200"
C020802	2"	713.32	60	1,500	103.9	400	2.375"	1.939"	.218"

20 Ft. Lengths — Plain Ends, Belled Ends Available Sch 40 Not Recommended For Threading
 NOT RECOMMENDED FOR COMPRESSED AIR OR GAS